



TK302III

Ticket printer

TK302III is the most advanced ticket printer available on the market for applications that require durability and the latest technologies. The printer can be delivered with an optional barcode scanner to validate tickets with pre-printed barcodes. The optional barcode scanner makes the TK302III suitable for all ticketing applications where fraud risks are very high, as it improves access controls. The barcode scanner is positioned inside the printer for a secure and real time scanning process. TK302III is extremely fast: up to 200mm/s ticket printing speed. It prints different paper widths, from 20 to 82.5mm, and can be easily adjusted by the user. Ticket weight (in grams): from 80 to 255 g/m². TK302III has an Ethernet interface with Embedded Web Server, which allows you to remotely and fully control the printer and perform real time diagnostics. The embedded client mail system is capable of sending out emails automatically, to request support or simply a paper change.



CHARACTERISTICS

- Ethernet web server for remote printing and configuration
- Printing speed up to 200 mm/s
- Different ticket widths: from 20 to 82.5 mm
- Ticket weight (in grams): from 80 to 255 g/m²
- Embedded display on 2 lines
- Automatic and robust cutter for 1.5 million cuts
- 32 bit powerful processor, 266 MHz
- RAM up to 32 MB, on 32 MB flash memory
- SD expansion slot for an additional 2 GB memory
- COM/USB virtual SW emulator

FOCUS ON

- 1D and 2D barcode printing: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, AZTEC, QR CODE
- RS232 + USB + Ethernet interface
- Sensors: fully adjustable lower and upper optical sensor, to suit any ticket width. Ticket presence sensor
- Using the 2 Gb SD or the 8 Mb mass storage USB memory, you can easily upload True Font characters and logos with a simple drag and drop command, and you can the install them directly
- The external power supply can be removed to facilitate installation



OPTIONAL

- Internal barcode reader to validate pre-printed tickets with barcodes
- Plastic or metal ticket outlet chute
- Paper roll holder mount or fan-fold

TECHNICAL SHEET

| | |
|------------------------|---|
| Printing Method | Thermal with fixed head |
| Number of dots | 8 dots/mm |
| Resolution | 203 DPI |
| Printing (mm/sec) | 200 mm/sec |
| Character set | PC437, PC850, PC860, PC863, PC865, PC858 |
| Printing Format | Height and width from 1x to 8x, reverse, underlined, script, bold |
| Printing Direction | Straight, 90°, 180°, 270° |
| Paper width | From 20mm to 82.5mm (2mm step) |
| Paper weight | from 80 to 255 g/m ² |
| Emulation | CUSTOM/POS - SVELTA |
| Interfaces | RS232 / USB / Ethernet |
| Data Buffer | 64 KB |
| Flash Memory | 16 MB |
| Graphic Memory | Dynamic logo management (max 2MB graphic memory) |
| Drivers | Windows® (32/64 bit) – solo su richiesta WHQL e installazione silente; Linux (32/64 bit); Virtual COM (Linux o Windows 32/64 bit); OPOS; Android™; iOS |
| Software Tools | PrinterSet, CustomPowerTool, Status Monitor, EasyMyfare, EthLocator |
| Power supply | 220 Vac ± 10% |
| Medium consumption | 0.8A (12,5% dots turned on) |
| Head Life | 100Km /100M pulses |
| MCBF | over 1,500,000 cuts |
| Dimensions | 252.1 (L) x 192.6 (H) x 216 (W) mm |
| Weight | 4 Kg |

MODELS



911BB070100713
PRINTER TK302III ETH USB RS232



911BB070900713
PRINTER TK302III ETH USB RS232
BCR

Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 27 January 2023